CEMENT CLINKER

MILESTONE APPLICATION NOTE FOR ACID DIGESTION SK-GEOCHEMISTRY-002



SUMMARY

This method represents a guideline for the microwave acid digestion of Cement clinker samples with the Milestone ETHOS UP and ETHOS EASY systems. This procedure may need to be optimized to match your specific analytical goals.

INSTRUMENTATION

Milestone ETHOS UP or ETHOS EASY microwave units, SK-15 high-pressure rotor, T2 easyTEMP temperature control. Options T1 temperature control and P1 or P2 pressure control.

SAMPLE WEIGHT AND REAGENTS

Sample weight	Up to 250 mg
T. 1. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
	7 ml HNO3
Doggonto	7 HIL HINUS
Reagents	3 mL HBF4*

^{*} H3BO3 : HF = 0,4 g : 1 mL

MICROWAVE PROGRAM

Step	Time	T2	Power*
1	00:20:00	230°C	1800 W*
2	00:15:00	230°C	1800 W*

* POWER SETTINGS

The power of the system must be set according to the table below:

3 or less vessels 800 W	
3 or less vessels 800 W	
4-8 vessels 1200 W	
4-0 (633613 1200 10	
9-15 vessels 1800 W	
3 10 1000010 1000 11	



GENERAL PRECAUTIONS

Always use hand, eye and body protection when operating with the microwave system.

Subject to change without notice.
For additional information
please visit www.milestonesrl.com
or contact application@milestonesrl.com

